



HD 9/50-4 Cage

This product uses up to 500 bar of pressure to remove even the most stubborn dirt. The robust cage design provides all-round protection and enables safe crane loading. With sack-trolley principle for easy transportation.



1 High-performance crankshaft pump

- Reliable and durable Kärcher high-performance crankshaft pump ensures optimal pressure.

2 Safe storage

- Accessories and tools are stored in a protected compartment. This means that everything is always in its place.



HD 9/50-4 Cage

- Robust industrial gun
- Dry run protection (optional)

Technical data

Order no.		1.367-157.0
EAN code		4039784731028
Working pressure	bar / MPa	150 – max. 500 / 15 – max. 50
Flow rate	l/h	500 – 900
Inlet temperature	°C	max. 60
Fuel		Electric
Engine rating	kW	15
Current type	Ph / V / Hz	3 / 440 / 60
Pump type		Maximum performance Kärcher crankshaft pump
Weight without accessories	kg	150
Weight (with accessories)	kg	190
Dimensions (L × W × H)	mm	930 × 800 × 920

Equipment

Electro start		–
High-pressure hose	m	10 / Heavy duty
Spray gun		Industrial trigger gun
Stainless steel spray lance	mm	700
Flat jet nozzle		■
Safety valve		■
Elapsed time counter		■

■ Included in the scope of supply.

HD 9/50-4 CAGE

1.367-157.0

KÄRCHER


		Order no.	Length				Price	Description	
High-pressure hoses									
Pressure hose	1	6.391-848.0						650 bar, M 22 x 1.5	■
	2	6.391-856.0						650 bar, M 22 x 1.5.	□
	3	6.391-857.0							□
	4	6.391-020.0						Durable, abrasion-resistant and flexible multi-layer steel-reinforced hose with connection size M 22 x 1.5. Suitable for up to 640 bar working pressure.	□
	5	6.391-846.0						650 bar, M 22 x 1.5	□
	6	6.391-847.0						650 bar, M 22 x 1.5.	□
	7	6.391-019.0						Durable, abrasion-resistant and flexible multi-layer steel-reinforced hose with connection size M 22 x 1.5. Suitable for up to 620 bar working pressure.	□
Trigger guns									
Kärcher industry gun	8	4.775-824.0						650 bar - industrial spray gun with optimised flow. Robustness and durability for professional use. Food-safe and saltwater-resistant materials. Connector for HP hoses M 22 x 1.5.	■
Spray lances									
Spray lance	9	4.760-679.0						With nozzle holder.	■
	10	4.760-653.0							□
Jet pipe complete 1550 mm 65 MPa	11	4.760-675.3							□
Spray lance	12	4.760-677.0							□
Spray lance extension	13	4.760-699.0						Spray lance extension 800 mm, 65 MPa.	□
Power nozzles									
Flat jet nozzle	14	5.765-163.0						15° flat jet nozzle 15028 for high-pressure cleaner HD 9/50. Suitable for working pressures of up to 500 bar and 900 l/h (petrol, 60 Hz).	■
Point jet nozzle	15	5.765-160.0						Point jet nozzle 0028 for high-pressure cleaner HD 9/50. Suitable for working pressures of up to 500 bar and 900 l/h (petrol, 60 Hz).	□
Attachment kits									
ABS protection against dry run	16	2.641-922.0						For electric motors.	□
ABS protection against water shortage	17	2.851-028.0						ABS steering rollers.	□
Couplings and connectors									
Coupling	18	4.403-004.0						For joining and extending HD hoses. Connection 2 x M 22 x 1.5. Material: Stainless steel.	□
Grease for stainless steel threaded joints	19	6.280-180.0						Grease for stainless steel screw connections.	□
Single-jet rotary nozzles									
Power rotary jet repair kit F8	20	6.025-437.0						Repair kit for power rotary jet, order no. 6.415-915.0. Suitable for 500 bar pressure and 900 l/h water flow rate. Includes rotor, seat and O-ring (28 x 2).	□
Tool for changing rotor seat	21	6.025-233.0						For F3, F4, F1, F25.	□
Power Rotary Jet F8 030	22	6.415-069.0						500 bar, 1.05 mm, 900 l/h, M 20 x 1, stainless steel.	□
Repair set Power Rotary Jet F8 030	23	6.812-000.0						Repair set for Power Rotary Jet. Suitable for up to 500 bar pressure and water volume of 900 litres/hour. Incl. rotor, fitting and O-ring.	□

■ Included in the scope of supply. □ Available accessories.

HD 9/50-4 CAGE

1.367-157.0

KÄRCHER


		Order no.	Length					Price	Description	
Screw nozzles F21										
Dummy nozzle F21	24	6.025-237.0							F21 screw-on dummy nozzle. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir	25	6.025-222.0							Screw-on F21 sapphire round jet nozzle with a diameter of 0.70 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Pipe cleaning										
Foot valve for pipe cleaning	26	6.470-223.0							Foot valve for convenient and safe use of accessories for effective pipe cleaning.	<input type="checkbox"/>
Pipe cleaning nozzle standard 030 50MPa	27	4.765-013.0							Standard pipe cleaning nozzle for pipe cleaning hoses with G1/4" threaded connection. Nozzle configuration: 3x backward.	<input type="checkbox"/>
Pipe cleaning nozzle Four 030 50MPa	28	4.765-019.0							Quattro pipe cleaning nozzle (500/15) for pipe cleaning hoses with G1/4" threaded connection. The chisel point nozzle configuration is 3x backward and 1x forward.	<input type="checkbox"/>
Pipe cleaning nozzle, Rotor	29	5.763-095.0							Rotor pipe cleaning nozzle for pipe cleaning hoses with G1/4" threaded connection. Nozzle configuration: 3x backward.	<input type="checkbox"/>
Pipe cleaning hose	30	6.392-401.0							Flexible pressure hose (DN 8) for thorough pipe cleaning. 10 m long. Threaded connection for G1/4" nozzle.	<input type="checkbox"/>
	31	6.392-402.0							Flexible pressure hose (DN 8) for thorough pipe cleaning. With threaded connection for G1/4" nozzle and 20 m long.	<input type="checkbox"/>
	32	6.392-403.0							For through pipe cleaning: flexible, 30 m long pressure hose with threaded connection for G1/4" nozzle.	<input type="checkbox"/>
Surface cleaner										
Surface Cleaner FRI 50 Me	33	2.643-577.0							Surface cleaner for efficient cleaning of surfaces up to 500 bar and hot water cleaning up to 100°C. 4 convenient steering rollers. Specific nozzle kits must be ordered separately.	<input type="checkbox"/>
Nozzle package 015 FRI 50 Me	34	6.415-044.0							Nozzle kit specifically for FRI 50 Me Surface Cleaner. Nozzle size: 015.	<input type="checkbox"/>
Abrasive blaster										
Required adapter for abrasive blasters	35	5.401-325.0							M 20 x 1 IG to 9/16" UNF AG.	<input type="checkbox"/>
Abrasive sprayer	36	9.872-250.0							Abrasive spray head for wet sand blasting. Nozzle size: 3 x 0.6. Only includes spray head. Without hose and lance.	<input type="checkbox"/>
Replacement nozzle for abrasive blaster	37	6.025-346.0							Replacement nozzle for abrasive spray head made from boron carbide. Colour blue.	<input type="checkbox"/>
	38	9.886-550.0								<input type="checkbox"/>
Nozzle F98 for abrasive blaster	39	6.025-256.0							0.6 mm	<input type="checkbox"/>
Suction lance	40	6.025-258.0							For the suction of spray agents.	<input type="checkbox"/>
Abrasive material hose	41	6.025-308.0							Abrasive hose.	<input type="checkbox"/>
Mounting tool for nozzle set	42	6.025-257.0							For F98 nozzles.	<input type="checkbox"/>
Abrasive	43	6.025-309.0							25 kg, 0.5-1.00 mm, garnet sand.	<input type="checkbox"/>
	44	6.025-310.0							25 kg, 0.7-1.40 mm, garnet sand.	<input type="checkbox"/>
Multi-jet rotary nozzles										
Nozzle body	45	9.917-677.0							Rotary transmission lead-through with infinitely variable speed control. Includes protective pipe.	<input type="checkbox"/>
Nozzle carrier head TD09	46	9.899-828.0							6-jet nozzle carrier head for F21 nozzle. Suitable for working pressures of up to 3,000 bar. 35° spray angle, includes guard and flow conditioner.	<input type="checkbox"/>

■ Included in the scope of supply. □ Available accessories.